

## QF5 & QF9



Working pressure: 150-870kPa  
Max. Temperature: 40 °C  
Flow rate: ~6 lpm  
Nominal micron rating: 5  
Nominal capacity: ~33000 litres

### Warning !

For commercial use with cold water only. Scheduled maintenance is recommended. Xsential cannot be liable for system failures due to improper maintenance.

For correct operation of this appliance, it is essential that these installation and operating instructions be strictly observed.

Certified to Australian Watermark Standard. QR 5 and QF 9 series water filter systems and cartridges uses NSF certified activated carbon to reduce chlorine, taste and odour and other offensive contaminants in the water. It consistently provides clear, fresh, premium quality ingredient water for making ice or drinking water.

The cartridges are also made to fit into below filter systems. It provides the essential saving compromise the quality.

### Reduces

- Sediment
- Chlorine
- Unpleasant taste and odour
- Organic contaminants

### Brand

### Model

Baker	BR100, BR200
Bremer	CCE150
Coast Distributors	CD10, CD20
Comcater	CCE100
Waterlogic	Maxiflow QC3323, QC3223, QC3323P
Hoshizaki	HLF1, HLF20
Moffat	IM10100C
Puretec	ACT1000, ACT1000P
Sink Warehouse	WFAQ708
WFS	QC3533P, QC3536P

**Caution:** Do not use with water that is microbiologically unsafe or with water of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used on disinfected water that may contain filterable cysts.

